

View Online at https://aerobasegroup.com/nsn/3040-01-241-4776

### **Body Material:**

Steel, aisi c1015

First End Outside Diameter:

0.625 inches

### **Mounting Provision:**

Unthreaded mounting holes

#### **Tempurature Rating:**

-10.0 degrees fahrenheit

#### **Overall Height:**

2.500 inches

**Overall Width:** 

2.500 inches

#### Bore Diameter:

#### 2.000 inches

### Longest Horizontal Distance Between Mounting Centers:

3.375 inches

### Longest Vertical Distance Between Mounting Centers:

1.840 inches

### First End External Thread Length:

0.750 inches

### Compressed Length:

8.938 inches

### Extended Length:

12.938 inches

### Mounting Provision Arrangement Style:

Four hole rectangular

### **Pressure Rating:**

500.0 pounds per square inch

### Integral Valve Operation Method:

Hydraulic

### **Design Characteristics:**

Single acting single cylinder

### First Piston Rod End Style:

External threaded

### First Piston Rod End Thread Series Designator:

Unf

### First Piston Rod End Thread Diameter:

0.438 inches

### First Piston Rod End Thready Qty Per Inch (tpi):

20

# First Piston Rod End Thread Class:

2a



### First Piston Rod End Thread Direction:

Right-hand

## Mounting Type And Location:

Flange piston rod end

# Mounting Facility Diameter:

0.375 inches

# Port Location And Quantity:

2 center section

Port Style:

Gasket seal

### Port Thread Series Designator:

Unf

# Port Thread Diameter:

0.562 inches

### Port Thready Qty Per Inch (tpi):

18

## Port Thread Class:

2b

### **Special Features:**

W/ lipseal piston; ports require adapter fitting which is not provided

Shelf Life:

N/a

## Unit Of Measure:

---

# Demilitarization:

No

### Fiig:

A34200