NSN 3040-01-245-4718

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-245-4718

First End Style:

Circular grooved and externally threaded

First End Groove Width:

Between 0.1150 inches and 0.1350 inches

First End Groove Diameter:

Between 0.7400 inches and 0.7600 inches

End Similarity:

Not identical

Second End Style:

Circular grooved and splined (straight)

Second End Groove Width:

Between 0.0840 inches and 0.0860 inches

Second End Groove Diameter:

Between 1.5216 inches and 1.5221 inches

Overall Length:

Between 10.865 inches and 10.885 inches

First End Distance From End To Groove:

Between 0.615 inches and 0.635 inches

First End Diameter:

Between 0.8650 inches and 0.8850 inches

First End External Thread Length:

Between 0.615 inches and 0.635 inches

Second End Distance From End To Groove:

Between 1.022 inches and 1.042 inches

Second End Diameter:

Between 1.9700 inches and 1.9800 inches

Second End Spline Length:

Between 0.960 inches and 0.980 inches

Second End Spline Minor Diameter:

Between 1.7900 inches and 1.8000 inches

Second End Spline Major Diameter:

Between 1.7716 inches and 1.7721 inches

Step Quantity:

6

Second End Spline Quantity:

10

Largest Step Diameter:

Between 1.970 inches and 1.980 inches

Special Features:

8 circular grooves

Material:

Steel comp 8620h

NSN 3040-01-245-4718

Shouldered Shaft - Page 2 of 2



		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A23200