## NSN 3040-01-252-3832

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-252-3832 **Body Material:** Steel First End Outside Diameter: 1.000 inches **Tempurature Rating:** -10.0 degrees fahrenheit **Overall Height:** 5.500 inches **Overall Width:** 5.500 inches **Bore Diameter:** 5.000 inches First End External Thread Length: 1.125 inches **Compressed Length:** 25.750 inches **Extended Length:** 43.750 inches **Pressure Rating:** 250.0 pounds per square inch **Features Provided:** Clevis pin and cushioned stroke **Integral Valve Operation Method:** Pneumatic **Design Characteristics:** Single acting single cylinder First Piston Rod End Style: External threaded First Piston Rod End Thread Series Designator: Unf First Piston Rod End Thread Diameter: 0.750 inches First Piston Rod End Thready Qty Per Inch (tpi): 16 **First Piston Rod End Thread Class:** 2a **First Piston Rod End Thread Direction:** Right-hand **Mounting Type And Location:** 

Mounting Type And Location
Fork cylinder head end
Port Location And Quantity:

2 center section

## NSN 3040-01-252-3832

Linear Actuating Cylinder Assembly - Page 2 of 2



Port Style:
Gasket seal
Port Thread Series Designator:
Unf
Port Thread Diameter:
0.750 inches
Port Thready Qty Per Inch (tpi):
16
Port Thread Class:
2b
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A34200