

View Online at <https://aerobasegroup.com/nsn/3040-01-273-1178>

**Shoulder Width:**

Between 0.554 inches and 0.570 inches

**Shoulder Outside Diameter:**

Between 0.742 inches and 0.758 inches

**Hub Inside Diameter:**

Between 0.189 inches and 0.191 inches

**First End Hub Outside Diameter:**

Between 0.278 inches and 0.280 inches

**Distance From First End Hub To Shoulder:**

Between 0.555 inches and 0.571 inches

**Special Features:**

No.4-40 unc-2b mounting holes are aligned in the shoulder face 89.0 degrees min -91 degrees maximum apart 0.160 in.Min-0.200 in.Max deep on a 0.462 in.Min -0.478 in.Max dia; shoulder face and back and hub end are chamfered at 0.010 in.Min -0.050 in.Max44 degrees min-46 degrees max; shaft access is chamfered at 0.000 in.-0.040in.Max 44 deg.Min -46 degrees maximum both ends; hub is offset from center against shoulder by 0.013 in.Min, 0.017 degrees maximum to form an eccentric; securing hole qty: 1; o/a length: 1.117 in.Min, 1.133 in.Max; securing hole size: 4-40 unc-2b

**Material:**

Steel

**Material Specification:**

Comp 303 federal specification single material response

**Surface Treatment:**

Passivate

**Style Designator:**

Single hub w/ securing hol (s)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A523y0