## NSN 3040-01-275-2522

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-275-2522

Body Material:
Brass
First End Outside Diameter:
0.875 inches
Inside Diameter:
0.992 inches
Mounting Provision:
Threaded mounting holes
Longest Horizontal Distance Between Mounting Centers:
1.230 inches
Longest Vertical Distance Between Mounting Centers:
1.230 inches
Mounting Facility Thread Class:
3b
Mounting Facility Thread Direction:
Right-hand
First End External Thread Length:
0.937 inches
Compressed Length:
14.500 inches
Extended Length:
15.750 inches
Mounting Provision Arrangement Style:
Four hole square
Mounting Facility Thread Series Designator:
Unc
Mounting Facility Thread Diameter:
0.375 inches
Mounting Facility Thready Qty Per Inch (tpi):
18
Integral Valve Operation Method:
Hydraulic
Design Characteristics:
Single acting single cylinder
First Piston Rod End Style:
External threaded
First Piston Rod End Thread Series Designator:
Unc
First Piston Rod End Thread Diameter:
0.625 inches
First Piston Rod End Thready Qty Per Inch (tpi):

## NSN 3040-01-275-2522

Linear Actuating Cylinder Assembly - Page 2 of 2



First Piston Rod End Thread Class:
2a
Mounting Type And Location:
ug center section
Mounting Facility Thread Length:
0.906 inches
Port Location And Quantity:
2 center section
Port Style:
Socket w/brazing ring
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:

A34200