

View Online at <https://aerobasegroup.com/nsn/3040-01-275-2522>

**Body Material:**

Brass

**First End Outside Diameter:**

0.875 inches

**Inside Diameter:**

0.992 inches

**Mounting Provision:**

Threaded mounting holes

**Longest Horizontal Distance Between Mounting Centers:**

1.230 inches

**Longest Vertical Distance Between Mounting Centers:**

1.230 inches

**Mounting Facility Thread Class:**

3b

**Mounting Facility Thread Direction:**

Right-hand

**First End External Thread Length:**

0.937 inches

**Compressed Length:**

14.500 inches

**Extended Length:**

15.750 inches

**Mounting Provision Arrangement Style:**

Four hole square

**Mounting Facility Thread Series Designator:**

Unc

**Mounting Facility Thread Diameter:**

0.375 inches

**Mounting Facility Thready Qty Per Inch (tpi):**

18

**Integral Valve Operation Method:**

Hydraulic

**Design Characteristics:**

Single acting single cylinder

**First Piston Rod End Style:**

External threaded

**First Piston Rod End Thread Series Designator:**

Unc

**First Piston Rod End Thread Diameter:**

0.625 inches

**First Piston Rod End Thready Qty Per Inch (tpi):**

11

**First Piston Rod End Thread Class:**

2a

**Mounting Type And Location:**

Lug center section

**Mounting Facility Thread Length:**

0.906 inches

**Port Location And Quantity:**

2 center section

**Port Style:**

Socket w/brazing ring

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A34200