

View Online at <https://aerobasegroup.com/nsn/3040-01-275-2526>

Body Material:

Steel

First End Outside Diameter:

Between 0.874 inches and 0.876 inches

Inside Diameter:

Between 0.991 inches and 0.993 inches

Mounting Provision:

Threaded mounting holes

Bore Diameter:

Between 3.243 inches and 3.245 inches

Overall Diameter:

5.000 inches

Longest Horizontal Distance Between Mounting Centers:

2.750 inches

Longest Vertical Distance Between Mounting Centers:

6.500 inches

End Application:

Ssn688 class submarine

Mounting Facility Thread Class:

3b

Mounting Facility Thread Direction:

Right-hand

First End External Thread Length:

0.938 inches

Compressed Length:

14.500 inches

Extended Length:

15.750 inches

Mounting Provision Arrangement Style:

Four hole rectangular

Mounting Facility Thread Series Designator:

Unc

Mounting Facility Thread Diameter:

0.500 inches

Mounting Facility Thread Qty Per Inch (tpi):

13

Integral Valve Operation Method:

Hydraulic

Design Characteristics:

Single acting single cylinder

First Piston Rod End Style:

External threaded

First Piston Rod End Thread Series Designator:

Unc

First Piston Rod End Thread Diameter:

0.625 inches

First Piston Rod End Thread Qty Per Inch (tpi):

11

First Piston Rod End Thread Class:

2a

First Piston Rod End Thread Direction:

Right-hand

Mounting Type And Location:

Screw cylinder base

Mounting Facility Thread Length:

1.000 inches

Port Location And Quantity:

1 piston rod end

Port Style:

Streamlined with one brazing ring

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A34200