## NSN 3040-01-277-7482

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-277-7482

Body Material:
Steel, stainless
First End Outside Diameter:
0.437 inches
Mounting Provision:
Threaded mounting studs
Mounting Facility Length:
0.5000 inches
Bore Diameter:
1.500 inches
Body Outside Diameter:
1.560 inches
Overall Diameter:
1.560 inches
Seat Angle In Deg:
37.0
Mounting Facility Thread Direction:
Right-hand
First End External Thread Length:
0.4375 inches
Compressed Length:
3.690 inches
Extended Length:
5.690 inches
Mounting Provision Arrangement Style:
Single stud
Pressure Rating:
250.0 pounds per square inch
Mounting Facility Thread Series Designator:
Npt
Design Characteristics:
Double acting single cylinder
First Piston Rod End Style:
External threaded
First Piston Rod End Thread Series Designator:
Unf
First Piston Rod End Thread Diameter:
0.437 inches
First Piston Rod End Thready Qty Per Inch (tpi):
20

2a

**First Piston Rod End Thread Class:** 

## NSN 3040-01-277-7482

Linear Actuating Cylinder Assembly - Page 2 of 2



First Piston Rod End Thread Direction:
Right-hand
Mounting Type And Location:
Stud piston rod end
Err Default:
Err default
Port Location And Quantity:
1 piston rod end
Port Style:
High pressure flare
Port Thread Series Designator:
Npt
Port Pipe Thread Size:
0.125 inches
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Demilitarization: