## NSN 3040-01-281-1102

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-281-1102 **Body Material:** Steel First End Outside Diameter: 2.000 inches **Mounting Provision:** Unthreaded mounting holes **Bore Diameter:** 3.250 inches **Longest Horizontal Distance Between Mounting Centers:** 52.625 inches **Longest Vertical Distance Between Mounting Centers:** 5.875 inches First End External Thread Length: 2.250 inches **Compressed Length:** 58.812 inches **Extended Length:** 107.312 inches **Mounting Provision Arrangement Style:** Four hole rectangular **Integral Valve Operation Method:** Hydraulic **Design Characteristics:** Single acting single cylinder First Piston Rod End Style: External threaded First Piston Rod End Thread Series Designator: Unf First Piston Rod End Thread Diameter: 1.500 inches First Piston Rod End Thready Qty Per Inch (tpi): **First Piston Rod End Thread Class:** 2a **First Piston Rod End Thread Direction:** Right-hand **Mounting Type And Location:** Lug both ends **Mounting Facility Diameter:** 0.812 inches **Port Location And Quantity:** 

1 center section

## NSN 3040-01-281-1102

Linear Actuating Cylinder Assembly - Page 2 of 2



Port Style:
Gasket seal
Port Thread Series Designator:
Un
Port Thread Diameter:
1.312 inches
Port Thready Qty Per Inch (tpi):
12
Port Thread Class:
2b
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A34200