NSN 3040-01-284-9170

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-284-9170 **Body Material:** Steel First End Outside Diameter: 1.750 inches **Mounting Provision:** Pin **Mounting Facility Length:** 8.500 inches **Overall Height:** 6.375 inches **Overall Width:** 5.500 inches **Bore Diameter:** 4.000 inches First End External Thread Length: 2.000 inches **Compressed Length:** 29.188 inches **Extended Length:** 50.188 inches **Pressure Rating:** 3000.0 pounds per square inch **Integral Valve Operation Method:** Hydraulic **Design Characteristics:** Double acting single cylinder First Piston Rod End Style: External threaded First Piston Rod End Thread Series Designator: Unf First Piston Rod End Thread Diameter: First Piston Rod End Thready Qty Per Inch (tpi):

1.250 inches 12 **First Piston Rod End Thread Class:** 2a **First Piston Rod End Thread Direction:** Right-hand **Mounting Type And Location:** Trunnion center section **Mounting Facility Diameter:** 1.750 inches

NSN 3040-01-284-9170

Linear Actuating Cylinder Assembly - Page 2 of 2



Port Location And Quantity:
1 piston rod end
Port Style:
Gasket seal
Port Thread Series Designator:
Unf
Port Thread Diameter:
1.062 inches
Port Thready Qty Per Inch (tpi):
12
Port Thread Class:
2b
Special Features:
High load piston; center of trunnion pin 9.750 in.From rod end base
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A34200