## NSN 3040-01-290-0750

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-290-0750 **Body Material:** Steel First End Outside Diameter: 3.000 inches Second End Outside Diameter: 3.000 inches **Mounting Provision:** Pin **Mounting Facility Length:** 17.000 inches **Overall Height:** 8.500 inches **Overall Width:** 8.500 inches **Bore Diameter:** 7.000 inches First End External Thread Length: 3.500 inches **Compressed Length:** 34.500 inches **Extended Length:** 40.500 inches **Pressure Rating:** 2510.0 pounds per square inch **Integral Valve Operation Method:** Hydraulic **Design Characteristics:** Double acting single cylinder First Piston Rod End Style: External threaded First Piston Rod End Thread Series Designator: First Piston Rod End Thread Diameter: 2.250 inches First Piston Rod End Thready Qty Per Inch (tpi): First Piston Rod End Thread Class: 2a First Piston Rod End Thread Direction:

Right-hand **Piston Rod End Similarity:** 

Not identical

## NSN 3040-01-290-0750

Linear Actuating Cylinder Assembly - Page 2 of 2



Second Piston Rod End Style:	
Spherical	
Mounting Type And Location:	
Trunnion cylinder head end	
Mounting Facility Diameter:	
Between 2.498 inches and 2.500 inches	
Port Location And Quantity:	
1 piston rod end	
Port Style:	
Gasket seal	
Port Thread Series Designator:	
Unf	
Port Thread Diameter:	
0.750 inches	
Port Thready Qty Per Inch (tpi):	
16	
Port Thread Class:	
2b	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	

A34200