

View Online at <https://aerobasegroup.com/nsn/3040-01-301-3024>

Body Material:

Steel

First End Outside Diameter:

0.625 inches

Mounting Provision:

Unthreaded mounting holes

Overall Height:

2.000 inches

Overall Width:

2.000 inches

Bore Diameter:

1.500 inches

Longest Horizontal Distance Between Mounting Centers:

3.875 inches

Longest Vertical Distance Between Mounting Centers:

2.750 inches

First End External Thread Length:

0.750 inches

Compressed Length:

5.625 inches

Extended Length:

6.625 inches

Mounting Provision Arrangement Style:

Four hole rectangular

Pressure Rating:

250.0 pounds per square inch

Integral Valve Operation Method:

Pneumatic

Design Characteristics:

Double acting single cylinder

First Piston Rod End Style:

External threaded

First Piston Rod End Thread Series Designator:

Unf

First Piston Rod End Thread Diameter:

0.438 inches

First Piston Rod End Thready Qty Per Inch (tpi):

20

First Piston Rod End Thread Class:

2a

First Piston Rod End Thread Direction:

Right-hand

Mounting Type And Location:

Lug both ends

Mounting Facility Diameter:

0.375 inches

Port Location And Quantity:

1 piston rod end

Port Style:

Gasket seal

Port Thread Series Designator:

Un

Port Thread Diameter:

0.562 inches

Port Thread Qty Per Inch (tpi):

18

Port Thread Class:

2b

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A34200