## NSN 3040-01-301-4338

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-301-4338 **Body Material:** Steel First End Outside Diameter: 1.375 inches **Mounting Provision:** Unthreaded mounting holes **Overall Height:** 4.500 inches **Overall Width:** 4.500 inches **Bore Diameter:** 4.000 inches **Longest Horizontal Distance Between Mounting Centers:** 19.250 inches **Longest Vertical Distance Between Mounting Centers:** 5.500 inches First End External Thread Length: 1.625 inches **Compressed Length:** 21.875 inches **Extended Length:** 37.875 inches **Mounting Provision Arrangement Style:** Four hole rectangular **Pressure Rating:** 250.0 pounds per square inch **Integral Valve Operation Method:** Pneumatic **Design Characteristics:** Double acting single cylinder First Piston Rod End Style: External threaded First Piston Rod End Thread Series Designator: Uns First Piston Rod End Thread Diameter: 1.000 inches First Piston Rod End Thready Qty Per Inch (tpi): 14 First Piston Rod End Thread Class:

2a **First Piston Rod End Thread Direction:** 

Right-hand

## NSN 3040-01-301-4338

Linear Actuating Cylinder Assembly - Page 2 of 2



Mounting Type And Location:
Lug both ends
Mounting Facility Diameter:
0.500 inches
Port Location And Quantity:
1 piston rod end
Port Style:
Gasket seal
Port Thread Series Designator:
Unf
Port Thread Diameter:
0.875 inches
Port Thready Qty Per Inch (tpi):
14
Port Thread Class:
Port Thread Class: 2b
2b
2b Shelf Life:
2b Shelf Life: N/a
2b Shelf Life: N/a Unit Of Measure:
2b Shelf Life: N/a Unit Of Measure:
2b Shelf Life: N/a Unit Of Measure: Demilitarization: