NSN 3040-01-302-9098

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-302-9098 **Body Material:** Steel First End Outside Diameter: 0.625 inches **Mounting Provision:** Unthreaded mounting holes **Bore Diameter:** 1.500 inches **Longest Horizontal Distance Between Mounting Centers:** 13.375 inches **Longest Vertical Distance Between Mounting Centers:** 2.750 inches First End External Thread Length: 0.750 inches **Compressed Length:** 7.125 inches **Extended Length:** 8.125 inches **Mounting Provision Arrangement Style:** Four hole rectangular **Integral Valve Operation Method:** Pneumatic **Design Characteristics:** Double acting single cylinder First Piston Rod End Style: External threaded First Piston Rod End Thread Series Designator: Unf First Piston Rod End Thread Diameter: 0.438 inches First Piston Rod End Thready Qty Per Inch (tpi): **First Piston Rod End Thread Class:** 2a **First Piston Rod End Thread Direction:** Right-hand Piston Rod End Similarity: Identical **Mounting Type And Location:** Lug both ends

Mounting Facility Diameter: 0.375 inches

NSN 3040-01-302-9098

Linear Actuating Cylinder Assembly - Page 2 of 2



Port Location And Quantity:
1 piston rod end
Port Style:
Gasket seal
Port Thread Series Designator:
Npt
Port Pipe Thread Size:
0.438 inches
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A34200