

View Online at <https://aerobasegroup.com/nsn/3040-01-305-9953>

Body Material:

Steel

Mounting Provision:

Unthreaded mounting holes

Temperature Rating:

190.0 degrees fahrenheit

Bore Diameter:

2.500 inches

Longest Horizontal Distance Between Mounting Centers:

4.625 inches

Longest Vertical Distance Between Mounting Centers:

4.625 inches

End Application:

2420-01-196-0299

Compressed Length:

21.750 inches

Extended Length:

24.750 inches

Mounting Provision Arrangement Style:

Four hole square

Pressure Rating:

3000.0 pounds per square inch

Features Provided:

Cushioned stroke

Integral Valve Operation Method:

Hydraulic

Design Characteristics:

Single acting single cylinder

First Piston Rod End Style:

Internal threaded

First Piston Rod End Thread Series Designator:

Unf

First Piston Rod End Thread Diameter:

1.250 inches

First Piston Rod End Thread Qty Per Inch (tpi):

12

First Piston Rod End Thread Class:

3b

First Piston Rod End Thread Direction:

Right-hand

Mounting Type And Location:

Fork cylinder base

Mounting Facility Diameter:

0.562 inches

Port Location And Quantity:

2 cylinder head end

Port Style:

Gasket seal

Port Thread Series Designator:

Unf

Port Thread Diameter:

0.750 inches

Port Thready Qty Per Inch (tpi):

16

Port Thread Class:

2b

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A34200