NSN 3040-01-311-1705

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-311-1705 **Body Material:** Steel **Mounting Provision:** Threaded mounting holes **Overall Height:** 2.500 inches **Overall Width:** 2.500 inches **Bore Diameter:** 2.000 inches **Longest Horizontal Distance Between Mounting Centers:** 13.375 inches **Longest Vertical Distance Between Mounting Centers:** 0.875 inches Seat Angle In Deg: 37.0 **Mounting Facility Thread Class:** 2b **Mounting Facility Thread Direction:** Right-hand **Compressed Length:** 16.625 inches **Extended Length:** 27.750 inches **Mounting Provision Arrangement Style:** Four hole rectangular **Mounting Facility Thread Series Designator: Mounting Facility Thread Diameter:** 0.312 inches Mounting Facility Thready Qty Per Inch (tpi): **Integral Valve Operation Method:** Hydraulic **Design Characteristics:** Double acting single cylinder **Mounting Type And Location:** Lug both ends **Mounting Facility Thread Length:** 0.438 inches

Port Location And Quantity:

1 piston rod end

NSN 3040-01-311-1705

Linear Actuating Cylinder Assembly - Page 2 of 2



Port Style:
Flare
Port Thread Series Designator:
Nptf
Port Pipe Thread Size:
0.375 inches
Special Features:
Double rod extension
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A34200