NSN 3040-01-323-5939

Shouldered Shaft - Page 1 of 2

Unit Of Measure:



View Online at https://aerobasegroup.com/nsn/3040-01-323-5939 First End Style: Circular grooved First End Groove Width: 0.1200 inches First End Groove Diameter: 2.9400 inches **End Similarity:** Not identical Second End Style: Circular grooved **Second End Groove Width:** 0.1200 inches **Second End Groove Diameter:** 2.9400 inches **Overall Length:** Between 10.080 inches and 10.140 inches **End Application:** 2330-01-303-8832 m1000 chettl trailer First End Distance From End To Groove: 1.000 inches **First End Diameter:** Between 3.0380 inches and 3.0390 inches **Second End Distance From End To Groove:** 1.000 inches **Second End Diameter:** Between 2.9750 inches and 2.9760 inches Step Quantity: **Largest Step Diameter:** 3.039 inches **Surface Finish:** 32.0 microinches **Special Features:** Chamfer on second end, 0.060 in. By 30.0 deg; chamfer on right edge of groove on first end, 0.060 in. By 30.0 deg Material: Steel comp 1026 **Material Specification:** Astm a519, grade 1026 assn standard single material response or astm a513, type 5, grade 1026 assn standard single material response Shelf Life: N/a

NSN 3040-01-323-5939

Shouldered Shaft - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A23200