NSN 3040-01-326-0870

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-326-0870 **Body Material:** Steel First End Outside Diameter: 1.750 inches **Mounting Provision:** Unthreaded mounting holes **Overall Height:** 6.500 inches **Overall Width:** 6.500 inches **Bore Diameter:** 6.000 inches **Body Outside Diameter:** 4.000 inches **Longest Horizontal Distance Between Mounting Centers:** 41.370 inches **Longest Vertical Distance Between Mounting Centers: 7.880** inches Seat Angle In Deg: 37.0 First End External Thread Length: 2.000 inches **Compressed Length:** 58.935 inches **Extended Length:** 110.560 inches **Mounting Provision Arrangement Style:** Four hole rectangular **Pressure Rating:** 250.0 pounds per square inch **Features Provided:** Cushioned stroke **Integral Valve Operation Method:** Pneumatic **Design Characteristics:** Double acting single cylinder First Piston Rod End Style: External threaded First Piston Rod End Thread Series Designator: Unf

First Piston Rod End Thread Diameter:

1.500 inches

NSN 3040-01-326-0870

Linear Actuating Cylinder Assembly - Page 2 of 2



First Piston Rod End Thready Qty Per Inch (tpi):
12
First Piston Rod End Thread Class:
2a
First Piston Rod End Thread Direction:
Right-hand
Mounting Type And Location:
Lug both ends
Mounting Facility Diameter:
0.812 inches
Port Location And Quantity:
1 piston rod end
Port Style:
Flare
Port Thread Series Designator:
Nptf
Port Pipe Thread Size:
0.750 inches
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A34200