NSN 3040-01-326-0870

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-326-0870 **Body Material:** Steel First End Outside Diameter: 1.750 inches **Mounting Provision:** Unthreaded mounting holes **Overall Height:** 6.500 inches **Overall Width:** 6.500 inches **Bore Diameter:** 6.000 inches **Body Outside Diameter:** 4.000 inches **Longest Horizontal Distance Between Mounting Centers:** 41.370 inches **Longest Vertical Distance Between Mounting Centers: 7.880** inches Seat Angle In Deg: 37.0 First End External Thread Length: 2.000 inches **Compressed Length:** 58.935 inches **Extended Length:** 110.560 inches **Mounting Provision Arrangement Style:** Four hole rectangular **Pressure Rating:** 250.0 pounds per square inch **Features Provided:** Cushioned stroke **Integral Valve Operation Method:** Pneumatic **Design Characteristics:** Double acting single cylinder First Piston Rod End Style: External threaded First Piston Rod End Thread Series Designator: Unf

First Piston Rod End Thread Diameter:

1.500 inches

NSN 3040-01-326-0870

Linear Actuating Cylinder Assembly - Page 2 of 2



First Piston Rod End Thready Qty Per Inch (tpi):	
12	
First Piston Rod End Thread Class:	
2a	
First Piston Rod End Thread Direction:	
Right-hand	
Mounting Type And Location:	
Lug both ends	
Mounting Facility Diameter:	
0.812 inches	
Port Location And Quantity:	
1 piston rod end	
Port Style:	
Flare	
Port Thread Series Designator:	
Nptf	
Port Pipe Thread Size:	
0.750 inches	
Shelf Life:	
N/a	
Unit Of Measure:	
	
Demilitarization:	
No	
Fiig:	
A34200	