NSN 3040-01-332-8872



Shouldered Shaft - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3040-01-332-8872 First End Style: Tapered with flat **End Similarity:** Not identical Second End Style: Circular grooved and splined (straight) **Second End Groove Diameter:** 0.1960 inches **Overall Length:** 6.500 inches First End Taper Major Diameter: 0.4320 inches First End Taper Length: 0.1700 inches First End Flat Depth: 0.0590 inches First End Flat Length: 0.1860 inches First End Angle Between Keyways: 45.0 degrees **Second End Distance From End To Groove:** 1.0330 inches **Second End Diameter:** 0.8550 inches **Second End Spline Length:** 0.7500 inches **Second End Spline Minor Diameter:** 0.0625 inches **Second End Spline Major Diameter:** 0.8550 inches Step Quantity: **Second End Spline Quantity:** 16 **Largest Step Diameter:** 0.978 inches **Special Features:** Tapered end i/d 0.188 in.; includes drilled hole on side; spline end hole i/d 0.531 in.; aircraft model hh65a ac generator, p/n 82562-7 Material:

N/a

Steel

Shelf Life:

NSN 3040-01-332-8872

Shouldered Shaft - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A23200