NSN 3040-01-338-2412

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-338-2412 **Body Material:** Steel, stainless First End Outside Diameter: 1.500 inches **Mounting Provision:** Pin **Mounting Facility Length:** 8.000 inches **Overall Height:** 4.500 inches **Overall Width:** 4.500 inches **Bore Diameter:** 4.000 inches First End Hole Diameter: 0.750 inches First End Thickness At Mounting Holes: 1.250 inches **Compressed Length:** 27.938 inches **Extended Length:** 47.938 inches **Pressure Rating:** Between 70.0 pounds per square inch and 150.0 pounds per square inch **Integral Valve Operation Method:** Pneumatic **Design Characteristics:** Double acting single cylinder First Piston Rod End Style: Ring type **Mounting Type And Location:** Trunnion center section **Mounting Facility Diameter:** 1.000 inches **Port Location And Quantity:** 1 piston rod end Port Style: Gasket seal **Port Thread Series Designator:**

Unjf

Port Thread Diameter:

0.875 inches

NSN 3040-01-338-2412 Linear Actuating Cylinder Assembly - Page 2 of 2



Port Thready Qty Per Inch (tpi):
14
Port Thread Class:
Bb
Criticality Code Justification:
-eat
Special Features:
Neapon system essential
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Fiig:

A34200