## NSN 3040-01-356-2706



Linear Actuating Cylinder Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3040-01-356-2706 **Body Material:** Brass First End Outside Diameter: 1.000 inches **Mounting Provision:** Pin **Mounting Facility Length:** 2.438 inches **Bore Diameter:** 4.000 inches **Body Outside Diameter:** 4.375 inches **Overall Diameter:** 4.375 inches **Mounting Facility Thread Direction:** Right-hand First End External Thread Length: 1.875 inches **Compressed Length:** 40.312 inches **Extended Length:** 70.312 inches **Pressure Rating:** Between 150.0 pounds per square inch and 350.0 pounds per square inch Mounting Facility Thready Qty Per Inch (tpi): 12 **Integral Valve Operation Method:** Hydraulic **Design Characteristics:** Double acting single cylinder First Piston Rod End Style: External threaded First Piston Rod End Thread Series Designator: Unf First Piston Rod End Thread Diameter: 1.000 inches First Piston Rod End Thready Qty Per Inch (tpi): 14 First Piston Rod End Thread Direction:

Right-hand

**Mounting Type And Location:** 

Tongue cylinder head end

## NSN 3040-01-356-2706

Linear Actuating Cylinder Assembly - Page 2 of 2



Mounting Facility Thread Length:
2.000 inches
Port Location And Quantity:
2 center section
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A34200