NSN 3040-01-363-2434

Mounting Provision:

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-363-2434

Unthreaded mounting holes
Overall Height:
2.000 inches
Overall Width:
2.500 inches
Bore Diameter:
2.000 inches
Longest Horizontal Distance Between Mounting Centers:
8.625 inches
Longest Vertical Distance Between Mounting Centers:
1.625 inches
First End External Thread Length:
1.250 inches
Compressed Length:
10.813 inches
Extended Length:
13.313 inches
Mounting Provision Arrangement Style:
Four hole rectangular
Pressure Rating:
150.0 pounds per square inch
Integral Valve Operation Method:
Pneumatic
Design Characteristics:
Double acting single cylinder
First Piston Rod End Style:
External threaded
First Piston Rod End Thread Series Designator:
Unc
First Piston Rod End Thread Diameter:
0.625 inches
First Piston Rod End Thready Qty Per Inch (tpi):
11
First Piston Rod End Thread Direction:
Right-hand
Mounting Type And Location:
Lug both ends
Mounting Facility Diameter:
0.344 inches
Port Location And Quantity:

2 center section

NSN 3040-01-363-2434 Linear Actuating Cylinder Assembly - Page 2 of 2



Port Style:
Gasket seal
Port Thread Series Designator:
Anpt
Port Pipe Thread Size:
0.250 inches
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A34200