NSN 3040-01-366-9584

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-366-9584 **Body Material:** Steel **Mounting Provision:** Unthreaded mounting holes **Overall Height:** 5.000 inches **Overall Width:** 3.000 inches **Bore Diameter:** 2.000 inches **Longest Horizontal Distance Between Mounting Centers:** 2.050 inches **Longest Vertical Distance Between Mounting Centers:** 4.125 inches **End Application:** Weapons elevator system and aviation engine storm hatch **Mounting Provision Arrangement Style:** Four hole rectangular **Pressure Rating:** 1650.0 pounds per square inch **Features Provided:** Cushioned stroke First Piston Rod End Style: External threaded First Piston Rod End Thread Series Designator: Unf First Piston Rod End Thread Diameter: 0.750 inches First Piston Rod End Thready Qty Per Inch (tpi): 16 **First Piston Rod End Thread Class:** Piston Rod End Similarity: Not identical **Mounting Type And Location:** Flange cylinder base **Mounting Facility Diameter:** 0.563 inches **Port Location And Quantity:** 1 cylinder base1 cylinder head end

Port Style:

Flare single portflare all ports

NSN 3040-01-366-9584

Linear Actuating Cylinder Assembly - Page 2 of 2



Port Thread Series Designator:
Unun
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Fiig:

A34200

Yes - demil/mli