NSN 3040-01-389-6791

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-389-6791

First End Style:

Circular grooved woodruff keyway and externally threaded

First End Groove Width:

0.0950 inches

First End Groove Diameter:

0.4400 inches

End Similarity:

Not identical

Second End Style:

Circular grooved and splined (straight)

Second End Groove Diameter:

Between 0.4450 inches and 0.4550 inches

Overall Length:

7.293 inches

First End Distance From End To Groove:

0.548 inches

First End Keyway Width:

Between 0.1240 inches and 0.1250 inches

First End External Keyway Length:

0.875 inches

First End Distance From Keyway Center To End:

1.126 inches

First End Diameter:

Between 0.4260 inches and 0.4310 inches

First End External Thread Length:

0.500 inches

Second End Distance From End To Groove:

0.400 inches

Second End Diameter:

Between 0.6826 inches and 0.6926 inches

Second End Spline Length:

0.400 inches

Second End Spline Major Diameter:

Between 0.8450 inches and 0.8500 inches

Step Quantity:

a

Second End Spline Quantity:

16

Largest Step Diameter:

Between 0.973 inches and 0.975 inches

Material:

Steel comp 4340

NSN 3040-01-389-6791

Shouldered Shaft - Page 2 of 2



Material Specification

Aisi4340 assn standard single material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A23200