

View Online at <https://aerobasegroup.com/nsn/3040-01-411-6254>

First End Style:

Circular grooved and externally threaded

First End Groove Width:

0.0600 inches

First End Groove Diameter:

0.4530 inches

End Similarity:

Not identical

Second End Style:

Circular grooved and flat keyway

Second End Groove Width:

0.0600 inches

Second End Groove Diameter:

0.4220 inches

Overall Length:

5.340 inches

First End Distance From End To Groove:

0.8200 inches

First End Diameter:

0.5620 inches

First End External Thread Length:

0.820 inches

Second End Distance From End To Groove:

0.5000 inches

Second End Keyway Width:

0.1250 inches

Second End External Keyway Length:

0.3750 inches

Second End Keyway Depth:

0.1100 inches

Second End Diameter:

0.4290 inches

Step Quantity:

7

Largest Step Diameter:

1.1670 inches

Surface Finish:

125.0 microinches

Special Features:

First end threads are 12unc-2a, splines near first end 30 teeth, pitch diameter .625; gear offcenter 12 teeth, pitch diameter 1.000; external threads at second end .562-24unef-2a

Material:

Stainless steel

Material Specification:

Mil-s-5626 cond-f-4 military specification single material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A23200

Mil-std (military Standard):

Mil-s-5626 spec.