

View Online at <https://aerobasegroup.com/nsn/3040-01-415-0999>

Body Material:

Any acceptable

First End Outside Diameter:

3.000 inches

Mounting Provision:

Unthreaded mounting holes

Tempurature Rating:

250.0 degrees fahrenheit

Overall Height:

9.750 inches

Overall Width:

7.000 inches

Bore Diameter:

5.000 inches

Body Outside Diameter:

7.000 inches

Longest Horizontal Distance Between Mounting Centers:

4.937 inches

Longest Vertical Distance Between Mounting Centers:

8.180 inches

End Application:

2350-01-390-4683; recovery vehicle, full tracked.

First End External Thread Length:

3.500 inches

Compressed Length:

35.000 inches

Extended Length:

56.500 inches

Mounting Provision Arrangement Style:

Four hole rectangular

Pressure Rating:

4000.0 pounds per square inch

Features Provided:

Piston rod

Design Characteristics:

Double acting single cylinder

First Piston Rod End Style:

External threaded

First Piston Rod End Thread Series Designator:

Unf

First Piston Rod End Thread Diameter:

2.250 inches

First Piston Rod End Thready Qty Per Inch (tpi):

12

First Piston Rod End Thread Class:

2a

First Piston Rod End Thread Direction:

Right-hand

Piston Rod End Similarity:

Not identical

Mounting Facility Diameter:

0.938 inches

Port Location And Quantity:

2 piston rod end

Port Style:

Gasket seal

Port Thread Series Designator:

Unf

Port Thread Diameter:

0.438 inches

Port Thready Qty Per Inch (tpi):

20

Port Thread Class:

2b

Special Features:

Must comply w/mil-c-52762a; 8000.0 psi proof pressure.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A34200