

View Online at <https://aerobasegroup.com/nsn/3040-01-416-3349>

Body Material:

Steel

First End Outside Diameter:

1.875 inches

Second End Outside Diameter:

1.250 inches

Mounting Provision:

Unthreaded mounting holes

Overall Height:

5.000 inches

Overall Width:

8.500 inches

Bore Diameter:

4.0000 inches

Longest Horizontal Distance Between Mounting Centers:

12.750 inches

Longest Vertical Distance Between Mounting Centers:

6.750 inches

First End External Thread Length:

3.000 inches

Second End External Thread Length:

2.000 inches

Compressed Length:

32.125 inches

Extended Length:

40.625 inches

Mounting Provision Arrangement Style:

Four hole rectangular

Integral Valve Operation Method:

Hydraulic

Design Characteristics:

Double acting single cylinder

First Piston Rod End Style:

External threaded

First Piston Rod End Thread Series Designator:

Un

First Piston Rod End Thread Diameter:

1.875 inches

First Piston Rod End Thread Qty Per Inch (tpi):

12

First Piston Rod End Thread Class:

1a

First Piston Rod End Thread Direction:

Right-hand

Piston Rod End Similarity:

Not identical

Second Piston Rod End Style:

External threaded

Second Piston Rod End Thread Series Designator:

Un

Second Piston Rod End Thread Diameter:

1.250 inches

Second Piston Rod End Thread Qty Per Inch (tpi):

12

Second Piston Rod End Thread Class:

1a

Second Piston Rod End Thread Direction:

Right-hand

Mounting Type And Location:

Lug cylinder base

Mounting Facility Diameter:

1.0625 inches

Port Location And Quantity:

1 piston rod end

Port Style:

Gasket seal

Port Thread Series Designator:

Un

Port Thread Diameter:

1.0625 inches

Port Thread Qty Per Inch (tpi):

12

Port Thread Class:

1b

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A34200