NSN 3040-01-417-2352

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-417-2352 **Body Material:** Steel First End Outside Diameter: 0.750 inches **Mounting Provision:** Pin **Mounting Facility Length:** 0.750 inches **Overall Width:** 2.500 inches **Bore Diameter:** 1.500 inches First End External Thread Length: 1.125 inches **Compressed Length:** 18.375 inches **Extended Length:** 28.375 inches **Integral Valve Operation Method:** Hydraulic **Design Characteristics:** Single acting single cylinder First Piston Rod End Style: External threaded First Piston Rod End Thread Series Designator: Unf First Piston Rod End Thread Diameter: 0.750 inches First Piston Rod End Thready Qty Per Inch (tpi): 16 **First Piston Rod End Thread Class: First Piston Rod End Thread Direction:** Right-hand **Mounting Facility Diameter:** 0.501 inches **Port Location And Quantity:** 1 piston rod end Port Style: Gasket seal

Unf

Port Thread Series Designator:

NSN 3040-01-417-2352

Linear Actuating Cylinder Assembly - Page 2 of 2



| Port Thread Diameter: |
|---------------------------------------|
| 0.875 inches |
| Port Thready Qty Per Inch (tpi): |
| 14 |
| Port Thread Class: |
| 1b |
| Special Features: |
| Clevis type mounting cylinder cap end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A34200