## NSN 3040-01-417-2363

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-417-2363 **Body Material:** Steel First End Outside Diameter: 2.250 inches **Mounting Provision:** Pin **Mounting Facility Length:** 2.500 inches **Overall Width:** 7.500 inches **Bore Diameter:** 6.000 inches First End External Thread Length: 3.500 inches **Compressed Length:** 57.125 inches **Extended Length:** 90.625 inches **Integral Valve Operation Method:** Hydraulic **Design Characteristics:** Single acting single cylinder First Piston Rod End Style: External threaded First Piston Rod End Thread Series Designator: Unf First Piston Rod End Thread Diameter: 2.250 inches First Piston Rod End Thready Qty Per Inch (tpi): 12 **First Piston Rod End Thread Class: First Piston Rod End Thread Direction:** Right-hand **Mounting Facility Diameter:** 2.001 inches **Port Location And Quantity:** 1 piston rod end Port Style:

Gasket seal

Port Thread Series Designator:
Unf

## NSN 3040-01-417-2363

Linear Actuating Cylinder Assembly - Page 2 of 2



| Port Thread Diameter:                 |
|---------------------------------------|
| 1.312 inches                          |
| Port Thready Qty Per Inch (tpi):      |
| 12                                    |
| Port Thread Class:                    |
| 1b                                    |
| Special Features:                     |
| Clevis type mounting cylinder cap end |
| Shelf Life:                           |
| N/a                                   |
| Unit Of Measure:                      |
|                                       |
| Demilitarization:                     |
| No                                    |
| Fiig:                                 |
| A34200                                |