NSN 3040-01-419-2643

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-419-2643 **Body Material:** Steel First End Outside Diameter: 0.750 inches **Mounting Provision:** Pin **Mounting Facility Length:** 1.250 inches **Overall Height:** 3.500 inches **Overall Width:** 3.500 inches **Bore Diameter:** 2.500 inches **End Application:** Ticonderoga class cg (47) First End External Thread Length: 1.125 inches **Compressed Length:** 20.453 inches **Extended Length:** 30.250 inches **Integral Valve Operation Method:** Hydraulic **Design Characteristics:** Single acting single cylinder First Piston Rod End Style: External threaded First Piston Rod End Thread Series Designator: Unf First Piston Rod End Thread Diameter: 0.750 inches First Piston Rod End Thready Qty Per Inch (tpi): 16 **First Piston Rod End Thread Class:** 2a **First Piston Rod End Thread Direction:** Right-hand **Mounting Facility Diameter:**

Port Location And Quantity:

1 piston rod end

0.750 inches

NSN 3040-01-419-2643

Linear Actuating Cylinder Assembly - Page 2 of 2



| Port Style: |
|----------------------------------|
| Gasket seal |
| Port Thread Series Designator: |
| Unf |
| Port Thread Diameter: |
| 0.562 inches |
| Port Thready Qty Per Inch (tpi): |
| 18 |
| Port Thread Class: |
| 1b |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A34200