NSN 3040-01-419-7124

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-419-7124 **Body Material:** Steel First End Outside Diameter: 0.750 inches **Mounting Provision:** Unthreaded mounting holes **Overall Height:** 5.125 inches **Overall Width:** 5.125 inches **Bore Diameter:** 2.000 inches **Longest Horizontal Distance Between Mounting Centers:** 4.125 inches **Longest Vertical Distance Between Mounting Centers:** 4.125 inches First End External Thread Length: 1.125 inches **Compressed Length:** 21.875 inches **Extended Length:** 27.875 inches **Mounting Provision Arrangement Style:** Four hole square **Integral Valve Operation Method:** Hydraulic **Design Characteristics:** Double acting single cylinder First Piston Rod End Style: External threaded First Piston Rod End Thread Series Designator: First Piston Rod End Thread Diameter: 0.750 inches First Piston Rod End Thready Qty Per Inch (tpi): First Piston Rod End Thread Class: 1a First Piston Rod End Thread Direction:

Right-hand

Piston Rod End Similarity:

Identical

NSN 3040-01-419-7124

Linear Actuating Cylinder Assembly - Page 2 of 2



Mounting Type And Location:
Flange cylinder head end
Mounting Facility Diameter:
0.562 inches
Port Location And Quantity:
1 piston rod end
Port Style:
Gasket seal
Port Thread Series Designator:
Unf
Port Thread Diameter:
0.875 inches
Port Thready Qty Per Inch (tpi):
14
Port Thread Class:
1b
Special Features:
Four additional mounting holes 2.050 in. Longest horizontal and vertical distance between mounting centers
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A34200