NSN 3040-01-422-4052

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-422-4052 **Body Material:** Steel **Mounting Provision:** Threaded mounting holes **Bore Diameter:** 2.000 inches **Longest Horizontal Distance Between Mounting Centers:** 4.125 inches **Longest Vertical Distance Between Mounting Centers:** 2.050 inches **End Application:** Nimitz class cvn **Mounting Provision Arrangement Style:** Four hole rectangular **Mounting Facility Thread Diameter:** 0.562 inches **Integral Valve Operation Method:** Hydraulic **Design Characteristics:** Single acting single cylinder First Piston Rod End Style: External threaded **Port Location And Quantity:** 1 piston rod end Port Style: Gasket seal **Port Thread Series Designator:** Unf **Port Thread Diameter:** 0.875 inches Port Thready Qty Per Inch (tpi): **Port Thread Class:** 1b **Special Features:** Rectangular flange mounting on cap end; tapped mounting on side Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 3040-01-422-4052

Linear Actuating Cylinder Assembly - Page 2 of 2



Fiig:

A34200