NSN 3040-01-422-5739

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-422-5739 **Body Material:** Steel First End Outside Diameter: 0.625 inches **Mounting Provision:** Pin **Mounting Facility Length:** 0.750 inches **Overall Height:** 2.500 inches **Overall Width:** 2.500 inches **Bore Diameter:** 1.500 inches First End External Thread Length: 0.750 inches **Compressed Length:** 14.125 inches **Extended Length:** 21.125 inches **Integral Valve Operation Method:** Hydraulic **Design Characteristics:** Single acting single cylinder First Piston Rod End Style: External threaded First Piston Rod End Thread Series Designator: Unf First Piston Rod End Thread Diameter: 0.438 inches First Piston Rod End Thready Qty Per Inch (tpi): **First Piston Rod End Thread Class:** 1a **First Piston Rod End Thread Direction: Mounting Facility Diameter: Port Location And Quantity:**

Right-hand 0.501 inches 1 piston rod end Port Style: Gasket seal

NSN 3040-01-422-5739

Linear Actuating Cylinder Assembly - Page 2 of 2



Port Thread Series Designator:
Unf
Port Thread Diameter:
0.875 inches
Port Thready Qty Per Inch (tpi):
14
Port Thread Class:
1b
Special Features:
Fixed clevis mounting cap end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A34200