

View Online at https://aerobasegroup.com/nsn/3040-01-422-7808

| Body Material: |
|--|
| Steel |
| First End Outside Diameter: |
| 1.750 inches |
| Mounting Provision: |
| Lugs |
| Bore Diameter: |
| 4.000 inches |
| End Application: |
| Nimitz class cvn |
| First End External Thread Length: |
| 2.000 inches |
| Integral Valve Operation Method: |
| Hydraulic |
| Design Characteristics: |
| Single acting single cylinder |
| First Piston Rod End Style: |
| External threaded |
| First Piston Rod End Thread Series Designator: |
| Unf |
| First Piston Rod End Thread Diameter: |
| 1.250 inches |
| First Piston Rod End Thready Qty Per Inch (tpi): |
| 12 |
| First Piston Rod End Thread Class: |
| 1a |
| First Piston Rod End Thread Direction: |
| Right-hand |
| Mounting Type And Location: |
| Lug both ends |
| Port Location And Quantity: |
| 1 piston rod end |
| Port Style: |
| Gasket seal |
| Port Thread Series Designator: |
| Un |
| Port Thread Diameter: |
| 1.062 inches |
| Port Thready Qty Per Inch (tpi): |
| 12 |
| Port Thread Class: |
| 1b |

1b

Linear Actuating Cylinder Assembly - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A34200