## NSN 3040-01-423-2886

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-423-288
Body Material:
Steel
Mounting Provision:
Unthreaded mounting holes and threaded mounting holes
Tempurature Rating:
-10.0 degrees fahrenheit
Overall Height:
2.500 inches
Overall Width:
Between 2.500 inches and 4.250 inches
Bore Diameter:
1.500 inches
Longest Horizontal Distance Between Mounting Centers:
3.438 inches
Longest Vertical Distance Between Mounting Centers:
1.630 inches
End Application:
Weapons system nimitz class cvn
Mounting Facility Thread Class:
2b
Mounting Facility Thread Direction:
Right-hand
Mounting Provision Arrangement Style:
Four hole rectangular
Pressure Rating:
3000.0 pounds per square inch
Mounting Facility Thread Series Designator:
Unc
Mounting Facility Thread Diameter:
0.375 inches
Mounting Facility Thready Qty Per Inch (tpi):
16
Integral Valve Operation Method:
Hydraulic
Design Characteristics:
Single acting single cylinder
First Piston Rod End Style:
External threaded
First Piston Rod End Thread Series Designator:
Unf
Mounting Type And Location:

**Mounting Type And Location:** 

Screw cylinder base

## NSN 3040-01-423-2886

A34200

Linear Actuating Cylinder Assembly - Page 2 of 2



Mounting Facility Thread Length:
0.375 inches
Mounting Facility Diameter:
0.438 inches
Special Features:
Threaded hole mounting position center to center length 79.875 in. Center to center width 0.750 in.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: