NSN 3040-01-423-2894

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-423-2894 **Body Material:** Steel **Mounting Provision:** Unthreaded mounting holes and threaded mounting holes **Tempurature Rating:** -10.0 degrees fahrenheit **Overall Height:** 2.500 inches **Overall Width:** Between 2.500 inches and 4.250 inches **Bore Diameter:** 1.500 inches **Longest Horizontal Distance Between Mounting Centers: 3.438** inches **Longest Vertical Distance Between Mounting Centers:** 1.630 inches **End Application:** Weapons system nimitz class cvn **Mounting Facility Thread Class:** 2b **Mounting Facility Thread Direction:** Right-hand **Mounting Provision Arrangement Style:** Four hole rectangular **Pressure Rating:** 3000.0 pounds per square inch **Mounting Facility Thread Series Designator:** Unc **Mounting Facility Thread Diameter:** 0.375 inches Mounting Facility Thready Qty Per Inch (tpi): **Integral Valve Operation Method:** Hydraulic **Design Characteristics:** Single acting single cylinder First Piston Rod End Style: External threaded First Piston Rod End Thread Series Designator:

Mounting Type And Location:

Screw cylinder base

NSN 3040-01-423-2894

A34200

Linear Actuating Cylinder Assembly - Page 2 of 2



Mounting Facility Thread Length:
0.375 inches
Mounting Facility Diameter:
0.438 inches
Special Features:
Threaded hole mounting position center to center length 79.875 in. Center to center width $0.750\mathrm{in}$.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: