NSN 3040-01-424-9080

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-424-9080
Body Material:
Steel
Mounting Provision:
Unthreaded mounting holes
Bore Diameter:
2.500 inches
Longest Horizontal Distance Between Mounting Centers:
4.625 inches
Longest Vertical Distance Between Mounting Centers:
2.550 inches
End Application:
Nimitz class cvn
Mounting Provision Arrangement Style:
Four hole rectangular
ntegral Valve Operation Method:
Hydraulic
Design Characteristics:
Single acting single cylinder
First Piston Rod End Style:
External threaded
Mounting Facility Diameter:
0.562 inches
Port Location And Quantity:
1 piston rod end
Port Style:
Gasket seal
Port Thread Series Designator:
Jnf
Port Thread Diameter:
0.875 inches
Port Thready Qty Per Inch (tpi):
14
Port Thread Class:
1b
Special Features:
Rectangular flange mounting on cap end; tapped mounting on side
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:

No

NSN 3040-01-424-9080

Linear Actuating Cylinder Assembly - Page 2 of 2



Fiig:

A34200