

View Online at <https://aerobasegroup.com/nsn/3040-01-424-9867>

Body Material:

Aluminum and steel

First End Outside Diameter:

0.437 inches

Mounting Provision:

Threaded mounting holes

Overall Height:

1.625 inches

Overall Width:

1.625 inches

Bore Diameter:

1.125 inches

Longest Horizontal Distance Between Mounting Centers:

1.188 inches

Longest Vertical Distance Between Mounting Centers:

1.188 inches

End Application:

Weapons system nimitz class cvn

Mounting Facility Thread Class:

1b

Mounting Facility Thread Direction:

Right-hand

First End External Thread Length:

0.750 inches

Compressed Length:

5.906 inches

Extended Length:

7.906 inches

Mounting Provision Arrangement Style:

Four hole square

Mounting Facility Thread Series Designator:

Unf

Mounting Facility Thread Diameter:

0.250 inches

Mounting Facility Thread Qty Per Inch (tpi):

28

Integral Valve Operation Method:

Hydraulic

Design Characteristics:

Double acting single cylinder

First Piston Rod End Style:

External threaded

First Piston Rod End Thread Series Designator:

Unf

First Piston Rod End Thread Diameter:

0.438 inches

First Piston Rod End Thread Qty Per Inch (tpi):

20

First Piston Rod End Thread Class:

1a

First Piston Rod End Thread Direction:

Right-hand

Mounting Type And Location:

Screw piston rod end

Mounting Facility Thread Length:

0.250 inches

Port Location And Quantity:

2 piston rod end

Port Style:

Gasket seal

Port Thread Series Designator:

Npt

Port Pipe Thread Size:

0.250 inches

Special Features:

2.000 in. Stroke, universal mount, used in hoist stroke control, deck control stand assembly

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A34200