## NSN 3040-01-425-6845

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-425-6845 **Body Material:** Steel First End Outside Diameter: 0.750 inches **Mounting Provision:** Pin **Mounting Facility Length:** 1.250 inches **Overall Height:** 3.000 inches **Overall Width:** 3.000 inches **Bore Diameter:** 2.000 inches First End External Thread Length: 1.125 inches **Compressed Length:** 19.125 inches **Extended Length:** 29.125 inches **Integral Valve Operation Method:** Hydraulic **Design Characteristics:** Single acting single cylinder First Piston Rod End Style: External threaded First Piston Rod End Thread Series Designator: Unf First Piston Rod End Thread Diameter: 0.750 inches First Piston Rod End Thready Qty Per Inch (tpi): **First Piston Rod End Thread Class:** 1a **First Piston Rod End Thread Direction:** Right-hand **Mounting Facility Diameter:** 0.751 inches **Port Location And Quantity:** 

1 piston rod end Port Style: Gasket seal

## NSN 3040-01-425-6845

Linear Actuating Cylinder Assembly - Page 2 of 2



| Port Thread Series Designator:   |
|----------------------------------|
| Unf                              |
| Port Thread Diameter:            |
| 0.875 inches                     |
| Port Thready Qty Per Inch (tpi): |
| 14                               |
| Port Thread Class:               |
| 1b                               |
| Special Features:                |
| Fixed clevis mounting cap end    |
| Shelf Life:                      |
| N/a                              |
| Unit Of Measure:                 |
|                                  |
| Demilitarization:                |
| No                               |
| Fiig:                            |
| A34200                           |