NSN 3040-01-426-0321

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-426-0321

Body Material:

Steel

Mounting Provision:

Threaded mounting holes and unthreaded mounting holes

Tempurature Rating:

-10.0 degrees fahrenheit

Overall Height:

3.500 inches

Overall Width:

Between 3.500 inches and 5.625 inches

Bore Diameter:

2.500 inches

Longest Horizontal Distance Between Mounting Centers:

90.000 inches

Longest Vertical Distance Between Mounting Centers:

2.500 inches

End Application:

Weapons system nimitz class cvn

Mounting Facility Thread Class:

2b

Mounting Facility Thread Direction:

Right-hand

Mounting Provision Arrangement Style:

Four hole rectangular

Pressure Rating:

3000.0 pounds per square inch

Mounting Facility Thread Series Designator:

Unc

Mounting Facility Thread Diameter:

0.375 inches

Mounting Facility Thready Qty Per Inch (tpi):

11

Integral Valve Operation Method:

Hydraulic

Design Characteristics:

Single acting single cylinder

First Piston Rod End Thread Series Designator:

Unf

Mounting Type And Location:

Flange cylinder head end and screw cylinder base

Mounting Facility Thread Length:

0.500 inches

NSN 3040-01-426-0321

No Fiig: A34200

Linear Actuating Cylinder Assembly - Page 2 of 2



Mounting Facility Diameter:
0.562 inches
Special Features:
Flanged mounting c to c mtg holes vert 2.550 in. Horz 4.625 in.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: