# NSN 3040-01-426-4985

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-426-4985

# First End Style:

Circular grooved flat keyway and externally threaded

#### First End Groove Width:

Between 0.1250 inches and 0.1410 inches

#### First End Groove Diameter:

Between 1.4770 inches and 1.4790 inches

#### **End Similarity:**

Not identical

#### Second End Style:

Two flat keyways

#### **Overall Length:**

26.500 inches

#### **End Application:**

Nimitz class (cvn)

#### First End Distance From End To Groove:

Between 0.5940 inches and 0.5990 inches

#### First End Keyway Width:

Between 0.3120 inches and 0.3280 inches

# First End External Keyway Length:

Between 0.8500 inches and 0.8700 inches

# First End Keyway Depth:

Between 0.1560 inches and 0.1640 inches

### First End Diameter:

Between 1.5548 inches and 1.5830 inches

# First End External Thread Length:

Between 0.5940 inches and 0.5990 inches

# **Second End Keyway Width:**

Between 0.4380 inches and 0.4400 inches

#### Second End External Keyway Length:

2.7500 inches

# **Second End Keyway Depth:**

Between 0.2190 inches and 0.2200 inches

# Second End Diameter:

Between 1.7490 inches and 1.7500 inches

### Second End Angle Between Keyways:

Between 89.9 degrees and 90.0 degrees

# Step Quantity:

5

### **Largest Step Diameter:**

Between 2.4970 inches and 2.5030 inches

#### **Surface Finish:**

10.0 microinches

# NSN 3040-01-426-4985

Shouldered Shaft - Page 2 of 2



ate		

Steel

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A23200