NSN 3040-01-428-1728

Body Material:

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-428-1728

Steel
First End Outside Diameter:
1.750 inches
Mounting Provision:
Unthreaded mounting holes
Tempurature Rating:
-10.0 degrees fahrenheit
Overall Height:
5.000 inches
Overall Width:
5.000 inches
Bore Diameter:
4.000 inches
First End External Thread Length:
2.000 inches
Extended Length:
49.375 inches
Mounting Provision Arrangement Style:
Four hole rectangular
Pressure Rating:
3000.0 pounds per square inch
Integral Valve Operation Method:
Hydraulic
Design Characteristics:
Single acting single cylinder
First Piston Rod End Style:
External threaded
First Piston Rod End Thread Series Designator:
Unf
First Piston Rod End Thread Diameter:
1.250 inches
First Piston Rod End Thready Qty Per Inch (tpi):
12
Mounting Type And Location:
Lug cylinder head end and lug piston rod end
Mounting Facility Diameter:
0.688 inches
Special Features:
Mounting modification thrust key, c to c between mtg holes width 3.820 in., stroke 38 in.
Shelf Life:
N/a

NSN 3040-01-428-1728

Linear Actuating Cylinder Assembly - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A34200