## NSN 3040-01-435-5323

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-435-5323

View Online at https://aerobasegroup.com/nsn/3040-01-435-53	32
Body Material:	
Iron	
First End Outside Diameter:	
1.000 inches	
Mounting Provision:	
Unthreaded mounting holes	
Tempurature Rating:	
220.0 degrees fahrenheit	
Overall Width:	
5.500 inches	
Bore Diameter:	
3.250 inches	
<b>Longest Horizontal Distance Between Mounting Centers:</b>	
4.688 inches	
Longest Vertical Distance Between Mounting Centers:	
2.760 inches	
End Application:	
Weapons system iwo jima class lp	
First End External Thread Length:	
1.125 inches	
Compressed Length:	
7.125 inches	
Extended Length:	
9.125 inches	
Mounting Provision Arrangement Style:	
Four hole rectangular	
Pressure Rating:	
250.0 pounds per square inch	
Integral Valve Operation Method:	
Pneumatic	
Design Characteristics:	
Single acting single cylinder	
First Piston Rod End Style:	
External threaded	
First Piston Rod End Thread Series Designator:	
Un	
First Piston Rod End Thread Diameter:	
0.750 inches	
First Piston Rod End Thready Qty Per Inch (tpi):	
16	
First Piston Rod End Thread Class:	

2a

## NSN 3040-01-435-5323

Linear Actuating Cylinder Assembly - Page 2 of 2



First Piston Rod End Thread Direction:
Right-hand
Mounting Type And Location:
Flange cylinder head end
Mounting Facility Diameter:
0.438 inches
Port Location And Quantity:
1 piston rod end
Port Style:
Gasket seal
Port Thread Series Designator:
Nptf
Port Pipe Thread Size:
0.500 inches
Special Features:
Stroke 2 in.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A34200