NSN 3040-01-440-1339

First End Outside Diameter:

0.312 inches

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-440-1339

Mounting Provision:
Unthreaded mounting holes
Overall Height:
1.250 inches
Bore Diameter:
0.625 inches
Body Outside Diameter:
0.876 inches
Longest Horizontal Distance Between Mounting Centers:
0.876 inches
Longest Vertical Distance Between Mounting Centers:
0.876 inches
End Application:
Weapons system whidbey island class lsd
First End External Thread Length:
0.750 inches
Compressed Length:
6.250 inches
Extended Length:
7.250 inches
Mounting Provision Arrangement Style:
Four hole square
Design Characteristics:
Double acting single cylinder
First Piston Rod End Style:
External threaded
First Piston Rod End Thread Series Designator:
Unf
First Piston Rod End Thread Diameter:
0.312 inches
First Piston Rod End Thready Qty Per Inch (tpi):
24
First Piston Rod End Thread Class:
2a
First Piston Rod End Thread Direction:
Right-hand
Piston Rod End Similarity:
Identical

Mounting Type And Location:

Screw both ends

NSN 3040-01-440-1339

Linear Actuating Cylinder Assembly - Page 2 of 2



Mounting Facility Diameter:
0.188 inches
Port Style:
Gasket seal
Port Thread Series Designator:
Npt
Port Pipe Thread Size:
0.125 inches
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A34200