

View Online at <https://aerobasegroup.com/nsn/3040-01-459-4822>

Cam Width:

1.875 inches

Specific Use:

Turret an/mwq-503

Camlength:

1.000 inches

Thickness:

1.500 inches

Special Features:

Cam has two lobes, each beginning from a radius of 0.875 in to a peak radius of 1.000 in, from 297.0 degrees through 7.0 degrees for a total of 70.0 degrees duration of the first lobe, and 144.0 degrees through 247.0 degrees for a total of 103.0 degrees duration for the second lobe; 1.000 in opening through center; three 0.173 in diameter holes with 0.375 in by 0.070 in deep counterbore are spaced equal distance around surface of 1.500 in diameter hub; three more holes, 0.128 in diameter by 0.090 in deep are located on face of first lobe, centered on a 1.250 in circle, the first two holes are positioned at 45.0 degrees angles to the left and right of 0.0 degrees with the third hole located at 180.0 deg

Material:

Aluminum alloy 2024 or aluminum alloy 6061

Material Specification:

Qq-a-225/6 federal specification single material response or qq-a-225/8 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2, class 1 military specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A50800

Mil-std (military Standard):

Mil-a-8625 spec.