NSN 3040-01-467-0392

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-467-0392

First End Style:

Circular grooved

First End Groove Width:

Between 0.0290 inches and 0.0320 inches

First End Groove Diameter:

Between 0.4410 inches and 0.4450 inches

End Similarity:

Not identical

Second End Style:

Circular grooved and slotted

Second End Groove Width:

Between 0.0390 inches and 0.0420 inches

Second End Groove Diameter:

Between 0.4660 inches and 0.4700 inches

Overall Length:

7.250 inches

End Application:

Nsn2320-01-123-1610 light armored vehicle-air defense

Second End Slot Width:

0.2190 inches

First End Distance From End To Groove:

0.1250 inches

First End Diameter:

Between 0.4723 inches and 0.4726 inches

Second End Distance From End To Groove:

0.6690 inches

Second End Diameter:

Between 0.4989 inches and 0.4994 inches

Second End Slot Depth:

0.4420 inches

Step Quantity:

1

Largest Step Diameter:

Between 0.4989 inches and 0.4994 inches

Surface Finish:

125.0 microinches

Special Features:

First end has a 2nd identical circular groove 0.684 in. From its 1st circular groove; second end's circular groove is adjacent to a woodruff keyseat and a 2nd identical circular groove; nha gear box assembly

Material:

Steel comp 4140

Material Specification:

Astma322 assn standard single material response

NSN 3040-01-467-0392

Shouldered Shaft - Page 2 of 2



_				-		
C	h	0	Iŧ.		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A23200