

View Online at <https://aerobasegroup.com/nsn/3040-01-475-1231>

**Body Material:**

Steel

**Tempurature Rating:**

160.0 degrees fahrenheit

**Bore Diameter:**

1.5000 inches

**End Application:**

Torpedo tube, submerged, upr rh, mk69, mod 1; torpedo tube, submerged, upr lh, mk69, mod 2; torpedo tube, submerged, upr center rh, mk69, mod 3; torpedo tube, submerged, upr center la, mk69, mod 4; torpedo tube, submerged, lwr ctr rh, mk69, mod 5; torpedo tube, submerged, lwr ctr lh, mk69, mod6; torpedo tube, submerged, lwr rh, mk69, mod 7; torpedo tube, submerged, lwr left hand, mk69, mod8; slide valve hyd power cylinder

**Pressure Rating:**

3000.0 pounds per square inch

**Integral Valve Operation Method:**

Hydraulic

**Design Characteristics:**

Double acting single cylinder

**Mounting Type And Location:**

Flange cylinder base

**Product Name:**

Cyl, pwr slide v (drawing) slide valve power cylinder assembly

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A34200