## NSN 3040-01-475-8412

Shouldered Shaft - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3040-01-475-8412

First End Style:
Circular grooved and externally threaded
First End Groove Width:
0.2500 inches
First End Groove Diameter:
1.2500 inches
End Similarity:
Not identical
Second End Style:
Circular grooved and externally threaded
Second End Groove Width:
0.2500 inches
Second End Groove Diameter:
1.1400 inches
Overall Length:
68.090 inches
End Application:
PUMP-UN-IT,-CENT
First End Distance From End To Groove:
0.5000 inches
First End Diameter:
1.3750 inches
First End External Thread Length:
0.5000 inches
Second End Distance From End To Groove:
1.2500 inches
Second End Diameter:
1.2500 inches
Second End External Thread Length:
1.2500 inches
Step Quantity:
15
Largest Step Diameter:
3.1250 inches
Surface Finish:
32.0 microinches
Material:
Steel comp 410
Material Specification:
Qq-s-763, cl. 410, cond. T-hf federal specification single material response
Special Test Features:
Shall not contain functional mercury and/or be contaminated by mercury or mercury compounds; certain dimensions require special
documentation of inspection

## NSN 3040-01-475-8412

Shouldered Shaft - Page 2 of 2



## **Supplementary Features:**

$Twelve\ keyways\ and\ one\ hole;\ first\ end\ 1.375\text{-}12unf\text{-}3a\ l.H.\ Threads};\ small\ center\ drill\ for\ mfg\ purposes;$	second end 1.250-12unf-3a r.H.
Threads and internally 0.484 drill-1.50 deep, 0.625 drill-0.25 deep, and 0.562-12unc-3b tap to 1.19 in	

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A23200