NSN 3040-01-481-1667

Shouldered Shaft - Page 1 of 1

Fiig: A23200



View Online at https://aerobasegroup.com/nsn/3040-01-481-1667 First End Style: Externally threaded and woodruff keyway **End Similarity:** Not identical Second End Style: Externally threaded and woodruff keyway **Overall Length:** 13.4375 inches First End Keyway Width: 0.1250 inches First End Diameter: Between 0.6586 inches and 0.6640 inches First End External Thread Length: 0.3750 inches **Second End Keyway Width:** 0.1875 inches **Second End Diameter:** Between 0.7756 inches and 0.7810 inches Second End External Thread Length: 0.4375 inches Step Quantity: 14 **Largest Step Diameter:** Between 1.2310 inches and 1.2315 inches **Special Features:** 1st end has 2 keyways - no. 7 woodruff key cut in from end 5/64" deep as described and no. 9 woodruff key indented- 1 7/16" I x 3/16" w x 3/32" deep; 2nd end no. 9 woodruff key cut from end 5/64" deep; both ends threaded 32 unf-3a; nha alternating current motor Material: Steel comp 1141 **Material Specification:** Qq-s-637 federal specification single material response or c 1141 assn standard single material response Shelf Life: N/a **Unit Of Measure:** Demilitarization: No